



Camera

Signal System:	PAL/NTSC
Effective Pixels:	720(H)×480(V)
Min. Illumination:	0.01Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens:	5-50mm motorized VF lens, Angle of view: 59.8°-6.2°
Adjustment Range:	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Day& Night:	IR cut filter with auto switch
Wide Dynamic Range:	75dB
Video Frame Rate:	1080p@25fps/1080p@30fps
HD Video Output:	1 Analog HD output
Synchronization:	Internal Synchronization
S/N Ratio:	More than 62 dB
Up the Coax:	Support

Menu

Camera ID:	On/off (15 characters, position programmable)
Auto White Balance:	ATW/ AWC-SET/ Indoor/ Outdoor/ Manual
Private Mask:	On/Off, maximum 8 zones
Motion Detection:	On/Off, maximum 4 zones
BLC:	On/Off
AGC:	Support
Anti-flicker:	On/ Off
Language:	English/Chinese
Function:	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Scene:	Indoor, Outdoor, Indoor1, LOW-LIGHT

General

Operating Conditions:	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	24 V AC ± 10%, 12 V DC ± 10% (-C series support 100 - 240 V AC)
Power Consumption:	Max. 20W
Weather Proof:	IP66

SF-CV710LZWU-FTVI



Dimension: 313.5*100.8*107.3

Weight: 1700g