

SF-DM855ZWU-4KT



Camera

Image Sensor:	8.29 MP high performance CMOS
Effective Pixels:	3840 (H) × 2160 (V)
Shutter Time:	PAL: 1/12.5 s to 1/10,000 s NTSC: 1/15 s to 1/10,000 s
Lens Mount:	M12
Adjustment Range:	Pan: 0° to 360°, Tilt:0° to 75°, Rotate: 0° to 360°
Day& Night:	IR cut filter with auto switch
Video Frame Rate:	PAL: 8 MP@12.5fps, 5 MP@20fps, 4 MP@25fps, 1080p@25fps NTSC: 8 MP@15fps, 5 MP@20fps, 4 MP@30fps, 1080p@30fps
HD Video Output:	1 Analog HD output
Synchronization:	Internal Synchronization

Menu

D/N Mode:	Auto / Color / B/W
Auto White Balance:	Auto/Manual/Natural
BLC:	Support
Language:	English

General

Operating Conditions:	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Weather Proof:	IP67
IR Range:	Up to 80m
Communication :	Up the coax Protocol: HIKVISION-C(Coaxitron)
Dimension:	134.3 mm × 123.9 mm × 111.4 mm (5.29" × 4.88" × 4.39")
Weight:	Approx. 630 g (1.39 lb.)