

SF-HTVR6116-HEVC



Video/Audio Input

Analog and HD-TVI video input: 16-ch,BNC interface (1.0Vp-p, 75 Ω)connection

Supported camera types:

Support HDTVI input: 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25
Support AHD input: 1080P/25Hz, 1080P/30Hz, 720P/25Hz, 720P/30Hz
Support CVI input: 1080P/25Hz, 1080P/30Hz, 720P/25Hz, 720P/30Hz
Support CVBS input

IP Video Input:

8-ch(up to 24ch) Up to 6MP resolution

Video/Audio Output

CVBS Output:

1-ch,BNC(1.0Vp-p,75Ω),resolution:PAL:704x576,NTSC:704x480

Frame Rate:

Main stream:
When 1080p Lite mode not enabled:
For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps
For 1080p stream access: 1080p/720p@15fps; VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)
For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)
When 1080p Lite mode enabled:
3 MP@15fps
1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)
Sub-stream:
WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)

Network management

Remote connections:

128

Network protocols:

TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF

General

Power Supply:

12 VDC

Consumption:

≤ 25W(without hard disks)

Working Temperature:

-10 °C to +55 °C (14 °F to 131 °F)

Working Humidity:

10% to 90%

Dimensions:

315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)

Weight:

≤ 2 kg (4.4 lb)