



Camera

Image Sensor:	8.29 MP high performance CMOS
Signal System:	PAL/NTSC
Effective Pixels:	3840 (H) × 2160 (V)
Min. Illumination:	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Lens Mount:	M16
Adjustment Range:	Pan: 0° to 360°, Tilt:0° to 180°, Rotate: 0° to 360°
Day& Night:	IR cut filter
Synchronization:	Internal Synchronization

Lens

Horizontal Field of View:	102.2°(2.8 mm), 79° (3.6 mm), 50.8° (6 mm)
----------------------------------	--

Menu

D/N Mode:	Auto/Color/BW (Black and White)
BLC:	Support
AGC:	Support
Language:	English
Function:	Brightness, Sharpness, DNR, Mirror, Smart IR

Interface

Video Out:	1 HD analog output
-------------------	--------------------

General

Material:	Metal
Operating Conditions:	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC±25%
IR Range:	Up to 30m
Communication :	Up the coax Protocol: Pelco-C(CVBS output), HIKVISION-C(TVI output)
Dimension:	90 mm × 79.37 mm (3.54" × 3.12")
Weight:	Approx. 310 g (0.68 lb.)